

强制性认证产品符合性自我声明

自我声明编号: 2020970304000245



Rockwell Automation, Inc. (生产者) 及 罗克韦尔自动化(中国)有限公司(生产者授权代表) 确认知晓《强制性产品认证自我声明实施规则》以及相关产品强制性认证实施规则的要求, 对本声明承担全部法律责任。

Rockwell Automation, Inc. (生产者) 及 罗克韦尔自动化(中国)有限公司(生产者授权代表) 声明以下产品已按照《强制性产品认证自我声明实施规则》以及相关产品强制性认证实施规则的要求进行检测, 符合相关标准要求; 自本声明签署之日起, 生产和销售的产品持续符合以下标准与实施规则的要求; 保存本声明涉及的技术文档至少10年; 正确使用强制性产品认证标志; 如产品或其符合性信息发生变更, 将及时更新技术文档并报送产品变更信息。

生产者名称: Rockwell Automation, Inc.
生产者地址: 1201 South Second Street, Milwaukee, WI 53204, USA
依据的强制性产品认证规则: CNCA-00C-008: 2019 强制性产品认证实施规则自我声明
产品名称: 接触器
产品系列、型号、规格: (见附页)
依据的标准: GB/T 14048.4-2020

序号	生产企业名称	生产企业地址
1	Rockwell Automation Switzerland GmbH	Industriestrasse 20, 5000 Aarau, Switzerland
2	Rockwell Automation, Inc.	1201 South Second Street, Milwaukee, WI 53204, USA
3	Rockwell Automation Sp. z o.o	UL. Rozdzienska 49, 40-382 Katowice, Poland
4	Rockwell Automation, Inc., Ladysmith	1506 East 16th Street South, Ladysmith, WI54848, USA
5	Rockwell Automation, B.V., Best Configuration Center	Brem 5, 5684 PB, Best, The Netherlands

生产者联系信息

名称: Rockwell Automation, Inc.
地址: 1201 South Second Street, Milwaukee, WI 53204, USA
联系人: 潘亮
电话: 021-61288888
电子邮箱: llpan@ra.rockwell.com
自我声明时间: 2022-03-31
自我声明地点: 上海
指定签字人:
签章:



授权代表信息

名称: 罗克韦尔自动化(中国)有限公司
地址: 上海市徐汇区虹梅路1801号宏业大厦
联系人: 潘亮
电话: 021-61288888
电子邮箱: llpan@ra.rockwell.com
自我声明时间: 2022-03-31
自我声明地点: 上海
指定签字人:
签章:



注: 有关本声明信息真伪可登录全国认证认可信息公共服务平台 (cx.cnca.cn) 或扫描右上角二维码查询。

强制性认证产品符合性自我声明(附页)

自我声明编号: 2020970304000245



产品系列、型号、规格:

100(S)-C09~97..., 104(S)-C09~97..., 100-CR09/12/16..., 100Q-C16/37..., CA(S/U/SU/Q)7-9~97..., CA7-R9/R12/R16..., 100-NX..., 10-00431..., 10-00503...; 型号解释及参数详见附录 Please refer to the appendix for explanation of catalog No. and specification

生产者联系信息

名称: Rockwell Automation, Inc.
地址: 1201 South Second Street, Milwaukee, WI 53204, USA
联系人: 潘亮
电话: 021-61288888
电子邮箱: llpan@ra.rockwell.com
自我声明时间: 2022-03-31
自我声明地点: 上海
指定签字人:
签 章:



授权代表信息

名称: 罗克韦尔自动化(中国)有限公司
地址: 上海市徐汇区虹梅路1801号宏业大厦
联系人: 潘亮
电话: 021-61288888
电子邮箱: llpan@ra.rockwell.com
自我声明时间: 2022-03-31
自我声明地点: 上海
指定签字人:
签 章:



注: 有关本声明信息真伪可登录全国认证认可信息公共服务平台 (cx.cnca.cn) 或扫描右上角二维码查询。



自我声明编号(CCC DoC No.): 2020970304000245

有效期(Period of Validity): 2020/03/26 - 2030/03/25

1. 基本信息(Basic Information):

生产者 (制造商)
(Manufacturer): Rockwell Automation, Inc.

生产者地址
(Address): 1201 South Second Street, Milwaukee, WI 53204, USA

生产企业
(Factory): 见生产企业一览表 Refer to list of factories

生产企业地址
(Address): 见生产企业一览表 Refer to list of factories

产品名称
(Product Name): 接触器 Contactor

型号
(Product Model/Type): 100(S)-C09~97..., 104(S)-C09~97...; 100-CR09/12/16...; 100Q-C16/37...; CA(S/U/SU/Q)7-9~97...; CA7-R9/R12/R16..., 100-NX..., 10-00431-..., 10-00503-...

适用标准
(Standards): GB/T 14048.4-2020

自我声明时间
(Date of Submission): 2022/03/31

备注(Note): 产品认证咨询请邮件联系(For consultation on product certification, please send e-mail to): productcertification@ra.rockwell.com

生产企业一览表(List of Factories): 适用时(If Applicable)

序号 (No.)	生产企业 (Name of Factory)	生产企业地址 (Address)	生产企业代码 (Factory Code)
1	Rockwell Automation Switzerland GmbH	Industriestrasse 20, 5000 Aarau, Switzerland	4030
2	Rockwell Automation, Inc.	1201 South Second Street, Milwaukee, WI 53204, USA	1050
3	Rockwell Automation Sp. z.o.o	UL. Rozdzienska 49, 40-382 Katowice, Poland	1170 or 1270
4	Rockwell Automation, Inc., Ladysmith	1506 East 16th Street South, Ladysmith, WI54848, USA	1080
5	Rockwell Automation, B.V., Best Configuration Center	Brem 5, 5684 PB, Best, The Netherlands	4010

注: 此附录与自我声明同时使用时有效。

Note: The appendix is valid when used together with corresponding CCC DoC.

自我声明编号(CCC DoC No.): 2020970304000245

有效期(Period of Validity): 2020/03/26 - 2030/03/25

2. 规格参数(Specification):

Ui: 690V;

Uimp: 6kV;

使用类别 Utilization category: 见下表 Refer to table below;

Ith: 见下表 Refer to table below;

Ue/Ie: 见下表 Refer to table below

UC	Type	09	12	16	23	30	37	43	55
AC-1	Ue (V)	≤690	≤690	≤690	≤690	≤690	≤690	≤690	≤690
	Ith (A)	32	32	32	32	65	65	85	85
AC-3	Ue (V)	230/240	230/240	230/240	230/240	230/240	230/240	230/240	230/240
	Ie (A)	12	15	20	26.5	35	38	44	56
	Ue (V)	400/415	400/415	400/415	400/415	400/415	400/415	400/415	400/415
	Ie (A)	9	12	16	23	30	37	43	55
	Ue(V)	500	500	500	500	500	500V	500	500
	Ie (A)	7	10	14	20	25	30	38	44
	Ue (V)	690	690	690	690	690	690V	690	690
	Ie (A)	5	7	9	12	18	21	25	25
AC-4	Ue (V)	230/240/400/ 415/500/690	230/240/400/ 415/500/690	230/240/400/ 415/500/690	230/240/400/ 415/500/690	230/240/400/ 415/500V/690	230/240/400/ 415/500V/690	230/240/400/ 415/500/690	230/240/400/ 415/500/690
	Ie (A)	4.3	6.6	9	9	12	14	16.5	22
UC	Type	60	72	85	97	R09	R12	R16	/
AC-1	Ue (V)	≤690	≤690	≤690	≤690	≤690	≤690	≤690	/
	Ith (A)	100	100	100	130	25	25	25	/
AC-3	Ue (V)	230/240	230/240	230/240	230/240	230/240	230/240	230/240	/
	Ie (A)	62	72	85	96/95	12	15	20	/
	Ue (V)	400/415	400/415	400/415	400/415	400/415	400/415	400/415	/
	Ie (A)	60	72	85	97	9	12	16	/
	Ue(V)	500	500	500	500	500	500	500	/
	Ie (A)	55	67	80	78	7	10	14	/
	Ue (V)	690	690	690	690	690	690	690	/
	Ie (A)	34	42	49	57	5	7	9	/
AC-4	Ue (V)	230/240/400/ 415/500/690	230/240/400/ 415/500/690	230/240/400/ 415/500/690	230/240/400/ 415/500/690	230/240/400/ 415/500/690	230/240/400/ 415/500/690	230/240/400/ 415/500/690	/
	Ie (A)	25.5	31	38	44	4.3	6.6	9	/
UC	Type	40	90						
AC-1	Ue (V)	≤690	≤690						
AC-1	Ith (A)	75	130						
AC-3	Ue (V)	230/240	230/240						
	Ie (A)	38	85						
AC-3	Ue (V)	400/415	400/415						
	Ie (A)	37	85						
	Ue(V)	500	500						
	Ie (A)	29(200)/30(400)	80						
	Ue (V)	690	690						
	Ie (A)	9(200)/21(400)	22(200)/49(400)						
	Ie (A)	9(200)/21(400)	22(200)/49(400)						
UC	Type								
AC-6b	Ith (A)								
	Ue (v)								
AC-6b	kVar								
	Ue (v)								
	kVar								
	Ue (v)								
	kVar								
	Ue (v)								
	kVar								

注: 此附录与自我声明同时使用时有效。

Note: The appendix is valid when used together with corresponding CCC DoC.



自我声明编号(CCC DoC No.): 2020970304000245

有效期(Period of Validity): 2020/03/26 - 2030/03/25

极数Poles: 3/4;

控制电压 Control voltage U_s :

AC: 12V50Hz, 12V60Hz, 24V50Hz, 24V60Hz, 24V50/60Hz, 20V50Hz/24V60Hz, 32V50Hz, 36V60Hz, 36V50Hz, 42V50Hz, 48V60Hz, 48V50Hz, 48V50/60Hz, 60V50/60Hz, 80V50/60Hz, 100V50Hz, 100V50/60Hz, 100...110V60Hz, 110V50Hz, 120V60Hz, 110V50/60Hz, 115V50Hz, 127V60Hz, 120V50Hz, 127V50Hz, 200V50Hz, 200V50/60Hz, 200...220V60Hz, 200...220V50Hz, 208...240V60Hz, 200...230V50/60Hz, 208V60Hz, 220...230V50Hz, 260V60Hz, 230V50/60Hz, 230...240V50Hz, 240V50Hz, 277V60Hz, 220V50Hz, 240V60Hz, 240V50/60Hz, 277V50/60Hz, 347V60Hz, 380V60Hz, 380...400V50Hz, 440V60Hz, 400...415V50Hz, 400V50/60Hz, 415V50/60Hz, 440V50/60Hz, 440V50Hz, 480V60Hz, 500V50Hz, 550V50Hz, 600V60Hz;

DC (Diode): 9V, 12V, 24V, 30V, 36V, 42V, 48V, 60V, 64V, 72V, 80V, 110V, 115V, 120V, 125V, 220V, 230V, 250V;

DC Electr. Coil: 12V, 24V, 36...48V, 48...72V, 110...125V, 220...250V, 24V(short drop-out time);

辅助触头 Auxiliary contacts (CCC DoC # 2020970305001013)

100-F..., 100S-F..., 100-CRF..., 100S-CRF..., 100-S..., 100-MC..., 100-FPT..., 100-FL11, CA7-PV..., CAS7-PV..., CS7-PV..., CSS7-PV..., CA7-RPV..., CAS7-RPV..., CS7-RPV..., CSS7-RPV..., CA7-PA..., CM7-..., CZE7-..., CZA7-..., CV7-11, 100-NX..., 10-00431-...;

Uimp: 6kV; Ui: 690V; Ith: 10A; IP20

AC-12: U_e/I_e : 690V/10A;

AC-15: U_e/I_e (100-F..., 100S-F..., 100-CRF..., 100S-CRF..., 100-S..., CA7-PV..., CAS7-PV..., CS7-PV..., CSS7-PV..., CA7-RPV..., CAS7-RPV..., CS7-RPV..., CSS7-RPV..., CA7-PA..., 100-NX..., 10-00431-...): 230V/5.5A, 240V/5A, 400V, 415V/3A, 500V/1.6A, 690V/1A;

U_e/I_e (100-F..., 100S-F..., 100-CRF..., 100S-CRF..., CA7-PV..., CAS7-PV..., CS7-PV..., CSS7-PV..., CA7-RPV..., CAS7-RPV..., CS7-RPV..., CSS7-RPV...): 230V, 240V/3A, 400/2A, 415V/2A, 500V/1.2A, 690V/0.7A

注: 此附录与自我声明同时使用时有效。

Note: The appendix is valid when used together with corresponding CCC DoC.

自我声明编号(CCC DoC No.): 2020970304000245

有效期(Period of Validity): 2020/03/26 - 2030/03/25

3. 型号的解释(Explanation of Catalog No.):

Allen-Bradley(A-B)									Sprecher + Schuh (S+S)						
100S-C	R	12	S	U	EJ	01	BC	X1	CA7-	R	12-	01	C-	U	24A
1	2	3	4	5	6	7	8	9	1	2	3	7	8	5	6

1 接触器基本分类 Base Catalogue Number

A-B	S+S	Options/Descriptions 含义
100-C	CA7-	IEC 接触器(3极和4极) IEC Contactor (3-poles and 4-poles)
100S-C	CAS7-	IEC 安全接触器(3极和4极) IEC Safety Contactor (3-poles and 4-poles)
100Q-C	CAQ7-	IEC 电容接触器(3极,仅16A和37A) IEC Capacitor Contactor (3-poles, sizes of 16A and 37A)
104-C	CAU7-	IEC 可逆接触器 IEC Reversing Contactor
104S-C	CASU7-	IEC 安全可逆接触器 IEC Safety Reversing Contactor

2 接线端子选项 Terminal Type

A-B	S+S	Options/Descriptions 含义
No Suffix	No Suffix	Screw terminal
R	R	Spring force terminals

3 接触器电流档选项 Contactor size

A-B	S+S	Options/Descriptions 含义
09	9(E/C/D) - ¹⁾	9A
12	12(E/C/D) - ¹⁾	12A
16	16(E/C/D) - ¹⁾	16A
23	23(E/C/D) - ¹⁾	23A
30	30(E/C/D) - ¹⁾	30A
37	37(E/C/D) - ¹⁾	37A
40	40(E/C/D) - ¹⁾	40A
43	43(E/C/D) - ¹⁾	43A
55	55(E/C/D) - ¹⁾	55A
60	60(E/C/D) - ¹⁾	60A
72	72(E/C/D) - ¹⁾	72A
85	85(E/C/D) - ¹⁾	85A
90	90(E/C/D) - ¹⁾	90A
97	97(E/C/D) - ¹⁾	97A

- 1) With suffix - E is for electronic 24V DC coil (S+S types only)
With suffix - C/D is for true DC coil (S+S types only)

4 功能布置 Function or Layout

A-B	S+S	Options/Descriptions 含义
No Suffix	Not applicable	Nothing specified
S	Not applicable	Coil with three field wiring terminals (for contactor sizes 9, 12, 16, 23, 30, 37)

注: 此附录与自我声明同时使用时有效。

Note: The appendix is valid when used together with corresponding CCC DoC.



自我声明编号(CCC DoC No.): 2020970304000245

有效期(Period of Validity): 2020/03/26 - 2030/03/25

5 线圈接线端子位置 Coil Terminal Position

A-B	S+S	Options/Descriptions 含义
No Suffix	No Suffix	Line side coil terminals
U	U	Load side coil terminals (bottom)

6 控制电压选项 Control Voltage Coil Code:

A-B	S+S	Options/Descriptions 含义 - AC
R	12A	12V50Hz
Q	12B	12V60Hz
K	24A	24V50Hz
J	24B	24V60Hz
KJ	24Z	24V50/60Hz
V	36	32V50Hz or 36V60Hz
W	36A	36V50Hz
X	48	42V50Hz or 48V60Hz
Y	48A	48V50Hz
KY	48Z	48V50/60Hz
KR	60Z	60V50/60Hz
KMA	80Z	80V50/60Hz
KP	110	100V50Hz or 100V50Hz/60Hz or 100-110V60Hz
D	120	110V50Hz or 120V60Hz
KD	110Z	110V50/60Hz
BC	127B	115V50Hz or 127V60Hz
P	120A	120V50Hz
S	127	127V50Hz
KG	220	200V50Hz or 200V50Hz/60Hz or 200-220V60Hz
L	220W	200-220V50Hz or 208-240V60Hz
KL	220Z	200-230V50/60Hz
H	208	208V60Hz
F	230A	220-230V50Hz or 260V60Hz
KF	230Z	230V50/60Hz
VA	240A	230-240V50Hz
T	277	240V50Hz or 277V60Hz
A	240	220V50Hz or 240V60Hz
KA	240Z	240V50/60Hz
KS	277Z	277V50/60Hz
I	347	347V60Hz
E	380B	380V60Hz
N	380	380-400V50Hz or 440V60Hz
G	415	400-415V50Hz
KN	400Z	400V50/60Hz
KU	415Z	415V50/60Hz
KB	440Z	440V50/60Hz
B	480	440V50Hz or 480V60Hz
M	500	500V50Hz
C	600	550V50Hz or 600V60Hz

A-B	S+S	Options/Descriptions 含义 - DC (Diode)
ZR or DR	9D or 9DD	9V
ZQ or DQ	12D or 9DD	12V
ZJ or DJ	24D or 9DD	24V
ZC or DC	30D or 9DD	30V
ZW or DW	36D or 9DD	36V
ZK or DK	42D or 9DD	42V
ZY or DY	48D or 9DD	48V
ZZ or DZ	60D or 9DD	60V
ZB or DB	64D or 9DD	64V
ZG or DG	72D or 9DD	72V
ZE or DE	80D or 9DD	80V
ZD or DD	110D or 9DD	110V
ZP or DP	115D or 9DD	115V
ZU or DU	120D or 9DD	120V
ZS or DS	125D or 9DD	125V
ZA or DA	220D or 9DD	220V
ZF or DF	230D or 9DD	230V
ZT or DT	250D or 9DD	250V

A-B	S+S	Options/Descriptions 含义 - DC Electr. Coil
EQ	12E	12V
EJ	24E	24V
EW	36E	36-48V
EY	48E	48-72V
ED	110E	110-125V
EA	220E	220-250V
QJ	24J	24V (short drop-out time)

Comments:

1. AC coil code (conventional AC coil: 12...550V50Hz, 12...600V60Hz, and 24...415V50/60Hz, double frequency).

注: 此附录与自我声明同时使用时有效。

Note: The appendix is valid when used together with corresponding CCC DoC.



自我声明编号(CCC DoC No.): 2020970304000245

有效期(Period of Validity): 2020/03/26 - 2030/03/25

2. DC coil code (conventional DC coil: 9...250V), two letters code starting with "Z" or "D"; "D" designates integrated bi-directional between coil terminals.
3. DC coil code (Electronical-controlled DC coil: 9...250V), two letters code starting with "E"; (electronical-controlled DC coil with reduced drop-out time: 12...250VDC), Two letter codes starting with "Q"; (Double Winding Coil: 9...110VDC), Two letter codes starting with "Y".
4. The coil codes listed on above table are for standard options, more options can be offered for customized demands when the main circuit and design keeps same.

7 主回路配置 Contact Configuration of Contactors:

A-B	S+S	Options/Descriptions 含义
00, 01, 02, 10, 11, 13, 14, 22, 23, 31, 32	00, 01, 02, 10, 11, 13, 14, 22, 23, 31, 32	Contact Configuration of Contactors (3-Poles)
200, 300, 400	M22, M31, M40	Contact Configuration of Contactors (4-poles)
11, 20	11, 20	Contact Configuration of Capacitor Switching Contactors
02, 22	02, 22	Contact Configuration of Reversing Contactors
02, 03, 04, 05, 11, 12, 13, 14, 21, 22, 23, 30, 31, 32, 40, 41, 50, 204, 222, 302, 304, 311, 313, 322, 331, 402, 404, 405, 411, 413, 414, 422, 423, 431, 432	02, 03, 04, 05, 11, 12, 13, 14, 21, 22, 23, 30, 31, 32, 40, 41, 50, 204, 222, 302, 304, 311, 313, 322, 331, 402, 404, 405, 411, 413, 414, 422, 423, 431, 432	Contact Configuration of Safety Contactors
008, 010, 012, 210	008, 010, 012, 210	Contact Configuration of Safety Reversing Contactors
-D00, -D01, -D02, -D10, -D11, -D20, -D00G, -D01G, -D02G, -D10G, -D11G, -D20G, -E00, -E01, -E10, -E00G, -E01G, -E10G, -200-D00, -300-D00, -400-D00, -200-D01, -300-D01, -400-D01, -200-D10, -300-D10, -400-D10, -200-D00G, -300-D00G, -400-D00G, -200-D01G, -300-D01G, -400-D01G, -D04, -D06, -D22, -D24, -D42, -E04, -E22	Not applicable	Contact Configuration of Contactors with Double Winding Coil (prefix "Y"): Prefix "D" is for contactors of sizes 09, 12, 16, 23 Prefix "E" is for contactors of sizes 30, 37, 43, 55 Suffix "G" designates that the coil switch-over contact is mounted to the left side of contactor; no suffix at this position designates that the coil switch-over contact is mounted to the right side of contactor
	Not applicable	Contact Configuration of Reversing Contactors with Double Winding Coil (prefix "Y") Prefix "D" is for reversing contactors of sizes 09, 12, 16, 23 Prefix "E" is for reversing contactors of sizes 30, 37, 43, 55

8 辅助回路布置 Auxiliary Contact Block

A-B	S+S	Options/Descriptions 含义
No Suffix	No Suffix	Regular auxiliary contact block
C	C	Auxiliary Contact Block on Safety (Reversing) Contactors with standard moveable contacts
BC	BC	Auxiliary Contact Block on Safety (Reversing) Contactors with bifurcated moveable contacts

注: 此附录与自我声明同时使用时有效。

Note: The appendix is valid when used together with corresponding CCC DoC.

自我声明编号(CCC DoC No.): 2020970304000245

有效期(Period of Validity): 2020/03/26 - 2030/03/25

9 辅助回路布置 Auxiliary Contact Block

A-B	S+S	Options/Descriptions 含义
No suffix	Not applicable	No option
-X1 / X1	Not applicable	Coil terminal entry from the side
-X2 / X2	Not applicable	Control wiring provided (Reversing Contactors only)
-X3 / X3	Not applicable	Terminal Covers not provided
-X6 / X6	Not applicable	Spade connectors provided (Reversing Contactors only)
-X50 / X50	Not applicable	Customized specific option
-15 / 15	Not applicable	Spade connectors provided (Contactors only)
-16 / 16	Not applicable	Spade connectors provided (Contactors only)
- M / M	Not applicable	Multipack (e.g. 20pcs)
-19B / 19B	Not applicable	Omit power wiring kit (Reversing Contactors only)

Allen Bradley(A-B)

100-NX	303	M
1	2	3

Carrier

10-00503-	00
1	2

1 Contactor type

A-B	Carrier	Contacteur type
100-NX	10-00431	Customized contactors for Carrier (100-NX228...236)
100-NX	10-00503	Customized contactors for Carrier (100-NX303...305)

2 Configuration

A-B	Carrier	Coil	Auxiliary Contact	Equivalent 100-C contactors
228	14	20V50Hz/24V60Hz	/	100-C12
229	01	20V50Hz/24V60Hz	/	100-C23
235	06	20V50Hz/24V60Hz	/	100-C12
236	07	20V50Hz/24V60Hz	/	100-C23
303	00	12V DC E-coil	1NC Auxiliary Contact (Built-in)	100-C12EQ01
304	10	12V DC E-coil	1NC Auxiliary Contact (Built-in)	100-C16EQ01
305	20	12V DC E-coil	1NC Auxiliary Contact (Built-in)	100-C23EQ01
310	30	12V DC E-coil	/	100-C30EQ00
311	31	12V DC E-coil	1NC Auxiliary Contact R.H. 100-SB01	100-C30EQ01
312	32	12V DC E-coil	1NC Auxiliary Contact R.H. 100-SB01	100-C30EQ01
320	40	12V DC E-coil	/	100-C37EQ00
321	41	12V DC E-coil	1NC Auxiliary Contact R.H. 100-	100-C37EQ01

注: 此附录与自我声明同时使用时有效。

Note: The appendix is valid when used together with corresponding CCC DoC.



自我声明编号(CCC DoC No.): 2020970304000245

有效期(Period of Validity): 2020/03/26 - 2030/03/25

			SB01	
322	42	12V DC E-coil	1NC Auxiliary Contact R.H. 100-SB01	100-C37EQ01
330	50	12V DC E-coil	/	100-C43EQ00
331	51	12V DC E-coil	1NC Auxiliary Contact R.H. 100-SB01	100-C43EQ01
332	52	12V DC E-coil	1NC Auxiliary Contact R.H. 100-SB01	100-C43EQ01

3 Package

A-B	Carrier	Contact type
M	--	20 piece Multi-pack
Blank	--	Single Packaging

Note: *100-NX "Carrier" brand labelled contactors are identical to 100-C contactors except different catalog number in nameplate.

Accessories

Auxiliary contact blocks: Refer to CCC DoC # 2020970305001013

Control Modules:

100-FPTA30: Pneumatic Timing Module, ON-Delay (.3 sec. - 30 sec.)
 100-FPTA180: Pneumatic Timing Module, ON-Delay (1.8 sec. - 180 sec.)
 100-FPTB30: Pneumatic Timing Module, OFF-Delay (.3 sec. - 30 sec.)
 100-FPTB180: Pneumatic Timing Module, OFF-Delay (1.8 sec. - 180 sec.)
 100-ETA3: Electronic Timing Module, ON-Delay (.1 sec. - 3 sec.)
 100-ETA30: Electronic Timing Module, ON-Delay (1 sec. - 30 sec.)
 100-ETA180: Electronic Timing Module, ON-Delay (10 sec. - 180 sec.)
 100-ETAZJ3: Electronic Timing Module, ON-Delay (.1 sec. - 3 sec.), 24V DC
 100-ETAZJ30: Electronic Timing Module, ON-Delay (1 sec. - 30 sec.), 24V DC
 100-ETAZJ180: Electronic Timing Module, ON-Delay (10 sec. - 180 sec.), 24V DC
 100-ETBKJ3: Electronic Timing Module, OFF-Delay (.1 sec. - 3 sec.), 24V 50/60Hz
 100-ETBKJ30: Electronic Timing Module, OFF-Delay (1 sec. - 30 sec.), 24V 50/60Hz
 100-ETBKJ180: Electronic Timing Module, OFF-Delay (10 sec. - 180 sec.), 24V 50/60Hz
 100-ETB3: Electronic Timing Module, OFF-Delay (.1 sec. - 3 sec.), 110-240 50/60Hz
 100-ETB30: Electronic Timing Module, OFF-Delay (1 sec. - 30 sec.), 110-240 50/60Hz
 100-ETB180: Electronic Timing Module, OFF-Delay (10 sec. - 180 sec.), 110-240 50/60Hz
 100-ETY30: Electronic Timing Module, Transition Time Y Contactor (1 sec. - 30 sec.), 110-240 50/60Hz
 100-MCA00: Interlock, Mechanical, no Auxiliary Contacts
 100-MCA02: Interlock, Mechanical/Electrical, 2 N.C. Auxiliary Contacts
 100-FL11*: Mechanical Latch, * refer table below:

注: 此附录与自我声明同时使用时有效。

Note: The appendix is valid when used together with corresponding CCC DoC.



自我声明编号(CCC DoC No.): 2020970304000245

有效期(Period of Validity): 2020/03/26 - 2030/03/25

Voltage	24V	48V	100V	110V	120V	230-240V	240V	277V	380-400V	400-415V	440V	480V
50 Hz	K	Y	KP	D	—	VA	KA	—	N	G	B	—
60 Hz	J	—	—	—	D	—	KA	T	—	—	N	B

100-JE12: Interface, Electronic (w/AC Coils Only) 12V DC

100-JE: Interface, Electronic (w/AC Coils Only)

100-JE48: Interface, Electronic (w/AC Coils Only) 48V DC

100-FSC48: Surge Suppressor, RC Module, 24...48V 50/60 Hz

100-FSC280: Surge Suppressor, RC Module, 110...280V 50/60 Hz

100-FSC480: Surge Suppressor, RC Module, 380...480V 50/60 Hz

100-FSV55: Surge Suppressor, Varistor Module, 12...55VAC / 12...77VDC

100-FSV136: Surge Suppressor, Varistor Module, 56...136VAC / 78...180VDC

100-FSV277: Surge Suppressor, Varistor Module, 137...277VAC / 181...350VDC

100-FSV575: Surge Suppressor, Varistor Module, 278...575VAC

100-FSD250: Surge Suppressor, Diode Module, 12...250VDC

Notes:

1. The explanation of catalog numbers above is only for reference of standard options, if any more configuration of catalog numbers for customized options existed, they will be covered by this certification if the configuration, material specification and electrical specification keeps same conditions.
2. Trademark: A-B is for Allen-Bradley, S+S is for Sprecher + Schuh.
3. Rockwell Automation's plant code is 4030, 1050, 1170/1270, 1080, 4010.

注: 此附录与自我声明同时使用时有效。

Note: The appendix is valid when used together with corresponding CCC DoC.