

强制性认证产品符合性自我声明

自我声明编号: 2020970302000496



Rockwell Automation, Inc. (生产者) 及 罗克韦尔自动化(中国)有限公司(生产者授权代表) 确认知晓《强制性产品认证自我声明实施规则》以及相关产品强制性认证实施规则的要求, 对本声明承担全部法律责任。

Rockwell Automation, Inc. (生产者) 及 罗克韦尔自动化(中国)有限公司(生产者授权代表) 声明以下产品已按照《强制性产品认证自我声明实施规则》以及相关产品强制性认证实施规则的要求进行检测, 符合相关标准要求; 自本声明签署之日起, 生产和销售的产品持续符合以下标准与实施规则的要求; 保存本声明涉及的技术文档至少10年; 正确使用强制性产品认证标志; 如产品或其符合性信息发生变更, 将及时更新技术文档并报送产品变更信息。

生产者名称: Rockwell Automation, Inc.
生产者地址: 1201 South Second Street, Milwaukee, WI 53204, USA
依据的强制性产品认证规则: CNCA-C03-02:2014 低压元器件
产品名称: 隔离开关
产品系列、型号、规格: (见附页)
依据的标准: GB/T14048.3-2017
生产企业名称: Rockwell Automation Sp. z o.o
生产企业地址: UL. Rozdzienska 49, 40-382 Katowice, Poland

生产者联系信息

名称: Rockwell Automation, Inc.
地址: 1201 South Second Street, Milwaukee, WI 53204, USA
联系人: 潘亮
电话: 021-61288888
电子邮箱: lpan@ra.rockwell.com
自我声明时间: 2020-04-28
自我声明地点: 上海
指定签字人: 
签章: 

授权代表信息

名称: 罗克韦尔自动化(中国)有限公司
地址: 上海市市辖区徐汇区虹梅路1801号宏业大厦
联系人: 潘亮
电话: 021-61288888
电子邮箱: lpan@ra.rockwell.com
自我声明时间: 2020-04-28
自我声明地点: 上海
指定签字人: 
签章: 

注: 有关本声明信息真伪可登录全国认证认可信息公共服务平台 (cx.cnca.cn) 或扫描右上角二维码查询。

强制性认证产品符合性自我声明(附页)



自我声明编号: 2020970302000496

产品系列、型号、规格:

194E-...40..., 194E-...63..., L. 7-40-..., L. 7-63-..., 194E-NX49; 参数及型号解释详见附件

生产者联系信息

名称: Rockwell Automation, Inc.
地址: 1201 South Second Street,
Milwaukee, WI 53204, USA
联系人: 潘亮
电话: 021-61288888
电子邮箱: llpan@ra.rockwell.com
自我声明时间: 2020-04-28
自我声明地点: 上海
指定签字人:
签 章:

授权代表信息

名称: 罗克韦尔自动化(中国)有限公司
地址: 上海市市辖区徐汇区虹梅路1801号宏业大厦
联系人: 潘亮
电话: 021-61288888
电子邮箱: llpan@ra.rockwell.com
自我声明时间: 2020-04-28
自我声明地点: 上海
指定签字人:
签 章:

注: 有关本声明信息真伪可登录全国认证认可信息公共服务平台 (cx.cnca.cn) 或扫描右上角二维码查询。

附录:

自我声明编号: 2020970302000496

1. 规格参数 (如适用):

194E-... 40..., 194E-... 63..., L. 7-40..., L. 7-63..., 194E-NX49;
194E-... 40..., L. 7-40-...;
 U_i : 690V; I_{th} : 63A; U_{imp} : 8kV;
AC-1, AC-21A: U_e/I_e : AC690V/40A;
AC-23A: U_e/I_e : AC230V/51A; AC400V/41A; AC690V/21A;
AC-3: U_e/I_e : AC230V/38A; AC400V/29A; AC690V/17A;
 I_{cw} : 1300A/1s; 额定限制短路电流: 20kA;
194E-... 63..., L. 7-63-...;
 U_i : 690V; I_{th} : 75A; U_{imp} : 8kV;
AC-1, AC-21A: U_e/I_e : AC690V/63A;
AC-23A: U_e/I_e : AC230V/61A; AC400V/55A; AC690V/24A;
AC-3: U_e/I_e : AC230V/51A; AC400V/35A; AC690V/21A;
 I_{cw} : 1300A/1s; 额定限制短路电流: 15kA (230V/400V), 10kA (690V);
使用类别: AC-21A, AC-23A, AC-1, AC-3; 极数: 3P-8P;
194E-NX49: U_i : 400/415V; I_{th} : 75A; U_{imp} : 8kV;
AC-21A: U_e/I_e : 400/415V/63A;
AC-23A: U_e/I_e : 230V/55A, 400/415V/55A;
 I_{cw} : 1300A/1s; 额定限制短路电流: 15kA;
使用类别: AC-21A, AC-23A; 极数: 3P; 外壳防护等级: IP54, IP66;
辅助触头: U_i : 690V; U_{imp} : 6kV; I_{th} : 12A;
AC-15: U_e/I_e : 120V/6A; 240V/3A; 380V/1.9A; 480V/1.5A; 500V/1.4A; 600V/1.2A;
DC-13: U_e/I_e : 125V/0.55A; 250V/0.27A; 400V/0.15A; 500V/0.13A; 600V/0.1A;

注: 此附录与自我声明同时使用时有效。

附录：

自我声明编号：2020970302000496

2. 型号的解释（如适用）：

1. Basic switch disconnectors

*	-	*	*	-	*
<i>1</i>		<i>2</i>	<i>3</i>		<i>4</i>

1	Product family, Basic Type		
	194E	-	Allen-Bradley types
	LA7	-	Sprecher + Schuh Type, A- Installation type
	LE7	-	Sprecher + Schuh Type, E- Installation type
2	Installation type		
	A	-	Allen-Bradley, Switch disconnecter for base/DIN-rail mounting
	E	-	Allen-Bradley, Switch disconnecter for front/door mounting
	Blank	-	Sprecher + Schuh selection
3	Load Size		
	40	-	40A
	63	-	63A
4	Function		
	1753	-	OFF/ON, 3-pole, 2-position
	1756	-	OFF/ON, 6-pole, 2-position
	1783	-	OFF/ON, 3-pole, 2-position, inverted
	3753	-	Changeover, 3-pole, 3-position

注：此附录与自我声明同时使用时有效。

附录:

第 3 页 共 7 页

自我声明编号: 2020970302000496

2. Handles

*	-	*	*	*	-	*
1		2	3	4		5

1 Product family, Basic Type	
194L	- Allen-Bradley
LFS2	- Sprecher + Schuh Type, Screw-mounting handle for use with front- and base-mounted switches
LFC2	- Sprecher + Schuh Type, mounting hole style handle for use with front-mounted switches
2 Installation type	
HC	- 22.5 mm mounting hole style handle for use with front-mounted switches
HE	- Screw-mounting handle for use with front- and base-mounted switches
Blank	- Sprecher + Schuh selection
3 Legend plate A-B	
4	- 48 mm x 48 mm
6	- 67 mm x 67 mm
8	- 88 mm x 88 mm
Legend plate S+S	
A	- Square, grey/black
I	- Square, red/yellow
E	- Square, lockable, grey/black
L	- Square, lockable, red/yellow
G	- Disc, lockable (up to 3 locks), grey/black
N	- Disc, lockable (up to 3 locks), red/yellow
4 Legend plate S+S	
A	- Square, grey/black
I	- Square, red/yellow
E	- Square, lockable, grey/black
L	- Square, lockable, red/yellow
G	- Disc, lockable (up to 3 locks), grey/black
N	- Disc, lockable (up to 3 locks), red/yellow
Legend plate A-B	
4	- 48 mm x 48 mm
6	- 67 mm x 67 mm
8	- 88 mm x 88 mm
5 Legend marking	
175	- 0 - 1
1751	- OFF - ON
350	- 1 - 0 - 2 (Reversing)
375	- 0 - 1 - 2 (90 degrees, changeover)
001	- No legend marking (code for mounting hole style handles only)

注: 此附录与自我声明同时使用时有效。

附录:

第 4 页 共 7 页

自我声明编号: 2020970302000496

3. Assembled switch disconnectors (open and enclosed types)

*	-	*	*	(-)	*	(-)	*	*	*
1		2	3		4		5	6	7

1 Product family, Basic Type	
194E	- Allen-Bradley types
LA7	- Sprecher + Schuh Type, A- Installation type
LE7	- Sprecher + Schuh Type, E- Installation type
LY7	- Sprecher + Schuh Type, Y,KA- Installation type
2 Installation type	
A	- Allen-Bradley, Base/DIN mounting, open type switch disconnecter
E	- Allen-Bradley, Front/door mounting, open type switch disconnecter
Y	- Allen-Bradley, Enclosed base mounting switch disconnecter (uses IP66 ABS thermoplastic enclosure)
KA	- Allen-Bradley, Enclosed base mounting switch disconnecter (uses IP66 polycarbonate (PC) enclosure)
Blank	- Sprecher + Schuh selection
3 Load Size	
40	- 40A
63	- 63A

注: 此附录与自我声明同时使用时有效。

附录:

第 5 页 共 7 页

自我声明编号: 2020970302000496

4	Configuration	
	1753	- 3-pole, OFF/ON
	1754	- 4-pole, OFF/ON
	1756	- 6-pole, OFF/ON
	3753	3-Pole, 3-Position (90°), Changeover
	Blank	- No options.
5	Handle A-B	
	4	- 48 mm x 48 mm
	6	- 67 mm x 67 mm
	Handle S+S	
	G	- Disc, lockable (up to 3 locks), grey/black
	N	- Disc, lockable (up to 3 locks), red/yellow
	A	- Square, grey/black
	Blank	- No options.
	Handle S+S	
	G	- Disc, lockable (up to 3 locks), grey/black
6	N	- Disc, lockable (up to 3 locks), red/yellow
	A	- Square, grey/black
	Blank	- No options.
	Handle A-B	
	4	- 48 mm x 48 mm
	6	- 67 mm x 67 mm

注: 此附录与自我声明同时使用时有效。

附录:

第 6 页 共 7 页

自我声明编号: 2020970302000496

4. Auxiliary contact blocks

*	-	*	-	*
1		2		3

1	Product family, Basic Type	
	194E	Allen-Bradley types
	LA7	Sprecher + Schuh Type, A- Installation type
	LE7	Sprecher + Schuh Type, E- Installation type
2	Installation type	
	A	Allen-Bradley, for use with A- Installation type
	E	Allen-Bradley, for use with E- Installation type
	Blank	Sprecher + Schuh selection
3	Contact configuration for Allen-Bradley	
	P11	1 NO + 1 NC
	PL11	1 NO + 1 NC late break
	P22	2 NO + 2 NC
	PD10	1 NO early closing
	Contact configuration for Sprecher + Schuh	
	P-11	1 NO + 1 NC
	P-L-11	1 NO + 1 NC late break
	P-22	2 NO + 2 NC
	P-D10	1 NO early closing

5. Additional poles

*	-	*	-	*
1		2		3

1	Product family, Basic Type		
	194E	-	Allen-Bradley types
	LA7	-	Sprecher + Schuh Type, A- Installation type
	LE7	-	Sprecher + Schuh Type, E- Installation type
2	Installation of Allen-Bradley		
	A40	-	for use with 194E-A40
	A63	-	for use with 194E-A63
	E40	-	for use with 194E-E40
	E63	-	for use with 194E-E63
	Installation of Sprecher + Schuh		
	40	-	for use with 40A
	63	-	for use with 63A
3	NP	-	Code for additional neutral pole (switched)

注: 此附录与自我声明同时使用时有效。

附录：

自我声明编号：2020970302000496

6. Grounding terminals, Neutral terminals

*	-	*	-	*
1		2		3

1	Product family, Basic Type		
	194E	-	Allen-Bradley types
	LA7	-	Sprecher + Schuh Type, A- Installation type
	LE7	-	Sprecher + Schuh Type, E- Installation type
2	Installation of Allen-Bradley		
	A63	-	for use with 194E-A40/A63
	E63	-	for use with 194E-E40/E63
	Installation of Sprecher + Schuh		
	63	-	for use with 40A and 63A
3	PE	-	Code for grounding terminal
	TN	-	Code for neutral terminal (not switched)

7. 194E-NX49

*	-	*
1		2

1	194E	-	Indicates product family	
2	NX49	-	Indicates basic switch disconnecter type 194E-A63-1753 with a padlockable red/yellow handle type 194L-HE4L-175L	

Notes:	1. The catalog breakdown is only for part of standard options, more of them and/or customized option are covered if the Configuration, material specification and electrical specification keeps same conditions.		
	2. The plant code is 1170 in Rockwell Automation's SAP system.		

注：此附录与自我声明同时使用时有效。