Certificate Number E54612

Report Reference E54612-20210730

Date 2021-August-05

Issued to: Rockwell Automation Switzerland GmbH

Industriestrasse 20 Aarau 5000 CH

This is to certify that representative samples of

MOTOR CONTROLLERS, MANUAL

See Addendum Page for Product Designation(s).

Have been investigated by UL in accordance with the

Standard(s) indicated on this Certificate.

Standard(s) for Safety: See Addendum Page for Standards

Additional Information: See the UL Online Certifications Directory at

https://iq.ulprospector.com for additional information

This Certificate of Compliance does not provide authorization to apply the UL Mark. Only the UL Follow-Up Services Procedure provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.





Certificate Number E54612

Report Reference E54612-20210730

Date 2021-August-05

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements

USL, CNL Manual Motor Controller, (NLRV, NLRV7)
Open type Manual Motor Controllers suitable as motor disconnect.

Cat. No. 140MT-C3E, followed by -A16, -A25, -A40, -A63, -B10, -B16, -B25, -B40, -B63, -C10, -C16, -C20, -C25, -C29, -C32.

Cat. No. 140MT-D9E, followed by –A63, -B10, -B16, -B25, -B40, -B63, -C10, -C16, -C20, -C25, -C29, -C32, -C36 or –C40.

Cat. No. 140MT-D9N, followed by -A16, -A25, -A40, -A63, -B10, -B16, -B25, -B40, -B63, -C10, -C16, -C20, -C25, -C29, -C32, -C36 or -C40.

Cat. No. 140MT-D9T, followed by -A16, -A25, -A40, -A63, -B10, -B16, -B25, -B40, -B63, -C10, -C16, -C20 or -C25.

Cat. No. 140MT-D9V, followed by -B16, -B25, -B40, -B63, -C10, -C16, -C20, -C25, -C29, -C32, -C36 or -C40.

Cat. No. KTA9-32S, followed by -0.16A, -0.25A, -0.40A, -0.63A, -1.0A, -1.6A, -2.5A, -4.0A, -6.3A, -10A, -16A, -20A, -25A, -29A, -32A.

Cat. No. KTA9-40H, followed by -0.63A, -1.0A, -1.6A, -2.5A, -4.0A, -6.3A, -10A, -16A, -20A, -25A, -29A, -32A, -36A or -40A.

Cat. No. KTB9-40H, followed by –0.16A, -0.25A, -0.40A, –0.63A, -1.0A, -1.6A, -2.5A, -4.0A, -6.3A, -10A, -16A, -20A, -25A, -29A, -32A, -36A or –40A.

Cat. No. KTC9-40H, followed by -0.16A, -0.25A, -0.40A, -0.63A, -1.0A, -1.6A, -2.5A, -4.0A, -6.3A, -10A, -16A, -20A or -25A.

Cat. No. KTV9-40H, followed by -1.6A, -2.5A, -4.0A, -6.3A, -10A, -16A, -20A, -25A, -29A, -32A, -36A or -40A.





Certificate Number E54612

Report Reference E54612-20210730

Date 2021-August-05

Standards:

UL 60947-4-1 - Low-Voltage Switchgear and Controlgear - Part 4-1: Contactors and Motor-Starters - Electromechanical Contactors and Motor-Starters

CSA C22.2 NO 60947-4-1-14 - Low-Voltage Switchgear and Controlgear - Part 4-1: Contactors and Motor-Starters - Electromechanical Contactors and Motor-Starters

UL 60947-1 - Low-Voltage Switchgear and Controlgear - Part 1: General Rules

CSA C22.2 NO 60947-1-13 - Low-Voltage Switchgear and Controlgear - Part 1: General Rules





UL LLC



Certificate Number UL-US-2138185-0

Report Reference E205542-20210804

Date 13-Aug-2021

Issued to: Rockwell Automation Switzerland GmbH

Industriestrasse 20 Aarau

Switzerland 5000

This is to certify that representative samples of

NKJH - Combination Motor Controllers

See Addendum Page for Product Designation(s).

Have been investigated by UL in accordance with the

Standard(s) indicated on this Certificate.

Standard(s) for Safety: UL 60947-1, 5th Ed., Issue Date: 2013-07-31, Revision

Date: 2019-05-06, UL 60947-4-1, 3rd Ed., Issue Date:

2014-04-04, Revision Date: 2017-10-17

Additional Information: See the UL Online Certifications Directory at

https://ig.ulprospector.com for additional information

This Certificate of Compliance does not provide authorization to apply the UL Mark. Only the UL Follow-Up Services Procedure provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.





 Certificate Number
 UL-US-2138185-0

 Report Reference
 E205542-20210804

Date 13-Aug-2021

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements

Model	Category Description
Combination Motor Controller, Cat. No. 140MT-C3E,,	Open Type Self-Protected
followed by –A16, -A25, -A40, -A63, -B10, -B16, -B25, -	- VIII-VIII-VIII-VIII-VI
B40, -B63, -C10, -C16.	<u>LVALVALVALVALV</u>
Combination Motor Controller, Cat. No. 140MT-D9E,	Open Type Self-Protected
followed by –A63, -B10, -B16, -B25, -B40, -B63, -C10, -	
C16, -C20, -C25, -C29, -C32, -C36 or -C40.	
Combination Motor Controller, Cat. No. 140MT-D9T,	Open Type Self-Protected
followed by –A16, -A25, -A40, -A63, -B10, -B16, -B25, -	
B40, -B63, -C10, -C16, -C20 or -C25.	. VII. VII. VII. VII. VI
Combination Motor Controller, Cat. No. 140MT-D9V,	Open Type Self-Protected
followed by -B16, -B25, -B40, -B63, -C10, -C16, -C20, -	
C25, -C29, -C32, -C36 or -C40.	
Combination Motor Controller, Cat. No. KTA9-32S,	Open Type Self-Protected
followed by -0.16A, -0.25A, -0.40A, -0.63A, -1.0A, -1.6A,	クークークークーク
-2.5A, -4.0A, -6.3A, -10A, -16A .	· × × × × ×
Combination Motor Controller, Cat. No. KTA9-40H,	Open Type Self-Protected
followed by -0.63A, -1.0A, -1.6A, -2.5A, -4.0A, -6.3A, -	
10A, -16A, -20A, -25A, -29A, -32A, -36A or –40A.	
Combination Motor Controller, Cat. No. KTC9-40H,	Open Type Self-Protected
followed by -0.16A, -0.25A, -0.40A, -0.63A, -1.0A, -1.6A,	1 X U1 X U1 X U1 X U1 X 1
-2.5A, -4.0A, -6.3A, -10A, -16A, -20A or -25A.	
Combination Motor Controller, Cat. No. KTV9-40H,	Open Type Self-Protected
followed by -1.6A, -2.5A, -4.0A, -6.3A, -10A, -16A, -20A,	. VII. VII. VII. VII. VI
-25A, -29A, -32A, -36A or –40A.	$L\Lambda^{\alpha}L\Lambda^{$





Certificate Number UL-CA-2131904-0

Report Reference E205542-20210804

Date 13-Aug-2021

Issued to: Rockwell Automation Switzerland GmbH

Industriestrasse 20 Aarau

Switzerland 5000

This is to certify that representative samples of

NKJH7 - Combination Motor Controllers Certified for

Canada

See Addendum Page for Product Designation(s).

Have been investigated by UL in accordance with the

Standard(s) indicated on this Certificate.

Standard(s) for Safety: CSA C22.2 NO. 60947-1-13, 2nd Ed., Issue Date: 2013-07-

31, CSA C22.2 NO. 60947-4-1, 2nd Ed., Issue Date: 2014-

04-04, Revised 2018-05

Additional Information: See the UL Online Certifications Directory at

https://iq.ulprospector.com for additional information

This Certificate of Compliance does not provide authorization to apply the UL Mark. Only the UL Follow-Up Services Procedure provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.





Certificate Number UL-CA-2131904-0
Report Reference E205542-20210804

Date 13-Aug-2021

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements

Model	Category Description
Combination Motor Controller, Cat. No. 140MT-C3E,,	Open Type Self-Protected
followed by –A16, -A25, -A40, -A63, -B10, -B16, -B25, -	
B40, -B63, -C10, -C16.	VALVALVALVALV
Combination Motor Controller, Cat. No. 140MT-D9E,	Open Type Self-Protected
followed by –A63, -B10, -B16, -B25, -B40, -B63, -C10, -	
C16, -C20, -C25, -C29, -C32, -C36 or -C40.	N UI X UI X UI X UI X
Combination Motor Controller, Cat. No. 140MT-D9T,	Open Type Self-Protected
followed by –A16, -A25, -A40, -A63, -B10, -B16, -B25, -	
B40, -B63, -C10, -C16, -C20 or -C25.	MII. MII. MII. MII. M
Combination Motor Controller, Cat. No. 140MT-D9V,	Open Type Self-Protected
followed by -B16, -B25, -B40, -B63, -C10, -C16, -C20, -	
C25, -C29, -C32, -C36 or -C40.	
Combination Motor Controller, Cat. No. KTA9-32S,	Open Type Self-Protected
followed by -0.16A, -0.25A, -0.40A, -0.63A, -1.0A, -1.6A,	
-2.5A, -4.0A, -6.3A, -10A, -16A.	XXXXX
Combination Motor Controller, Cat. No. KTA9-40H,	Open Type Self-Protected
followed by -0.63A, -1.0A, -1.6A, -2.5A, -4.0A, -6.3A, -	
10A, -16A, -20A, -25A, -29A, -32A, -36A or –40A.	
Combination Motor Controller, Cat. No. KTC9-40H,	Open Type Self-Protected
followed by -0.16A, -0.25A, -0.40A, -0.63A, -1.0A, -1.6A,	M ULM ULM ULM ULM
-2.5A, -4.0A, -6.3A, -10A, -16A, -20A or -25A.	
Combination Motor Controller, Cat. No. KTV9-40H,	Open Type Self-Protected
followed by -1.6A, -2.5A, -4.0A, -6.3A, -10A, -16A, -20A,	VII. VII. VII. VII. VI
-25A, -29A, -32A, -36A or –40A.	$\Lambda^{\circ}L\Lambda^{\circ$



