

CERTIFICATE OF COMPLIANCE

Certificate Number 20160728-E205542
Report Reference E205542-20101116
Issue Date 2016-JULY-28

Issued to: Rockwell Automation Switzerland GmbH
Industriestrasse 20
5000 Aarau SWITZERLAND

This is to certify that representative samples of COMBINATION MOTOR CONTROLLERS
See Addendum Page

Have been investigated by UL in accordance with the Standard(s) indicated on this Certificate.

Standard(s) for Safety: UL 60947-1 and CSA C22.2 No. 60947-1-13, Low Voltage Switchgear and Controlgear, Part 1: General Rules
UL 60947-4-1 and CSA C22.2 No. 60947-4-1-14, Low Voltage Switchgear and Controlgear, Part 4-1: Contactors and Motor Starters, Electromechanical Contactors and Motor-Starters

Additional Information: See the UL Online Certifications Directory at www.ul.com/database for additional information

Only those products bearing the UL Certification Mark should be considered as being covered by UL's Certification and Follow-Up Service.

Look for the UL Certification Mark on the product.



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



CERTIFICATE OF COMPLIANCE


Certificate Number 20160728-E205542
Report Reference E205542-20101116
Issue Date 2016-JULY-28

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Enclosed Type Combination Motor Controllers:

Cat. Nos. 103C or 107C, followed by -09, -12, or -16 followed by L, followed by Q, R, J, K, KJ, V, W, X, Y, KY, KP, D, KD, P, H, L, A, F, KF, T, E, N, KN, G, B, M, C, or 24E, followed by -C, -D or -XXX, may be followed by A16, A25, A40, A63, B10, B16, B25, B40, B63, C10, C16, C20 or C25, followed by B, C or X, may be followed by JE, -R, S01, S10, S11, S20, or -V, followed by -1M, -14RM, -3, -3E, 4G, 4R, or 4Y.

Cat. Nos. CX7 or CXU7, followed by -9, -12, -16, or -23, may be followed by E, followed by P, followed by 12A, 12B, 24A, 24B, 24E, 24Z, 32, 36, 42, 48A, 48Z, 110, 110Z, 120, 120A, 208, 220W, 230A, 230Z, 240, 240A, 380, 380B, 400Z, 415, 480, 500, or 600, followed by 01, 10, or 22, followed by AS or AH or -XXX, may be followed by 0.16A, 0.25A, 0.4A, 0.63A, 1.0A, 1.6A, 2.5A, 4.0A, 6.3A, 10A, 16A, 20A, or 25A, followed by A01, A10, A11, A20, T10A01, T10A10, or X, may be followed by C, V, JE, S01, S10, S11, or S20, followed by 1G, 1R, 1Y, 3, 3U, 4U, 5U, 6, 7, or 8, followed by G or J.



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>

